

Product Glance	Value
Product model	S11-20T
Hashrate, TH/s	20.00
Reference power efficiency on wall @25°C, J/TH	80.00
Power supply requirement, Watt/ Volt	1600 W / 220 V

Detailed Characteristics	Value		
	Min	Typ	Max
Hashrate & Power			
Hashrate, TH/s		20.00	20.45
Power efficiency on wall @25°C, J/TH	80.00		85.60
Power efficiency on wall @40°C, J/TH	85.90		91.91
Power on wall, Watt ⁽¹⁻¹⁾	1600		1880
Power supply AC input voltage, Volt ⁽¹⁻²⁾	200	220	240
Power supply AC input current, Amp ⁽¹⁻³⁾		7.27	9.40
Power supply Input AC Frequency Range, Hz	47	50	63
Hardware Configuration			
Quantity of hash chips	252		
Quantity of hash boards	3		
Networking connection mode	RJ45 ethernet 10/100M		
Miner Size (Length*Width*Height, w/o package), mm	254*176*297		
Net weight, kg	8.5		
Noise, dBA @25°C ⁽²⁻¹⁾		4.2	76
Environment Requirements			
Operation temperature, °C	0	25	40
Storage temperature, °C	-40	25	85
Operation humidity, RH	5%		95%